

C34S-X4 SPEC



System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.7inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.5Lux (Color mode) ,0.1Lux (B&W mode)
	Lens	2.8~12mm@F1.4 electronic optical Zoom+Focus
	View Angle	Support Zoom and Focus synchronously, Horizontal:103~30.8° , Vertical: 74.4~23.3° , Diagonal:130° ~40°
	Night vision	Dual Filter,IR-Cut, 6pcs 850nm Φ5mm IR LED , IR irradiation distance:30m
Video	Encode format	H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Three Stream	Main Stream:1080p(1920X1080)@15fps Sub Stream:360p(640X360)@15fps Third Stream:180p(320X180)@10fps
	Bit Rate	128~4096kbps
	Maximum frame rate	15fps
	Image adjustment	Contrast、Brightness、 Saturation、 Hue
	Audio	N/A
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan-tilt	Pan-tilt	Pan: 355°,tilt: 90°
	Preset position	PC APP: support 16 positions, Phone APP:support 5 positions
Memory	Socket	TF Push-push socket,Maximum support 128GB, Cloud Storage
Alarm	Alarm Trigger	Motion detection
Physical Environmental	Rated voltage	DC 12V±5%
	Power consumption	Related power:6.72W(IR LED on), Maximum power: 16.32W (Pan&Tilt&Zoom on)
	Operating condition	Temperature:-10~50°C,humidity:<90%
	Weight	Gross: 1555g(Note: in kind prevail)
	Package size	250*163*262mm (L×W×H)