



**Front Door**



**Rear Door**



**Side Panel**

## LINK RACK

Is premium innovation design, an Elegant appearance, delivered with best enterprise service, support and reliability. LINK RACK offered high strength product, high durability and efficiency at work

## CW-Series


- Curve wave hexa perforated at front door for bestest ventilation.
- Wave hexa perforate at rear door for bestest ventilation.
- Provide swing handle lock at front and rear door.
- I-frame for supporting the solid steel at side panels and easy to remove by slide lock and security lock for install and maintenance.
- Vented raised roof cover can be mounted the fan sets.
- Mounting pole with 10 x 10 mm. mounting hole adjustable in/out with U-height screened on pole.
- Up and down movable stand with Nylon six - castor turn 360 degree.
- Cable entry from the roof and the base with slide.
- All parts are modular knock down with grounding.

## Standards :

- Comply with ANSI/EIA-310D, IEC297-1, IEC297-2, BS5954 Part : 2, DIN 41494

U Height (U=44.45 mm.)	Width (mm.)	Depth (mm.)	Order Number
<b>15U</b>	600	600	CH-60615CW
	600	800	CH-60815CW
<b>27U</b>	600	600	CH-60627CW
	600	800	CH-60827CW
	600	900	CH-60927CW
<b>42U</b>	600	600	CH-60642CW
	600	800	CH-60842CW
	600	900	CH-60942CW
	600	1000	CH-61042CW
	600	1100	CH-61142CW
	800	800	CH-80842CW
	800	1000	CH-81042CW
	800	1100	CH-81142CW

# LINK RACK FEATURES



**Tempered Glass Door**  
Tempered Glass  
Perforated Steel



**Wave Door**  
Hexa Perforated  
for 110% Ventilation




**Curve Wave Door**  
Hexa perforated  
for 120% Ventilation



**Steel Door**  
Solid Steel without  
Hole for Protection



**Side Panel**  
Easy to Remove by Slide Lock  
and Security Lock



**Side Panel Support**  
I-Frame for Supping  
The Solid Steel




**Security Locks**  
Press and Swing  
Handel Lock



**Top Cover**  
Has the Clip  
for Cable Entry.



**Bottom Panel**  
Has Slide Shutter  
and the Clip for  
Cable Entry.



**Mounting Pole**  
U-Height Screened on Pole



**Castor & Stand**  
Up and Down Movable Stand and  
Nylon Six - Castor Turn 360 Degree



**Grounding**  
Connecting Between  
all Removable Part of Rack

**Material :**

- Frame - 2.0 mm galvanized steel
- Front Door - 1.2 mm galvanized steel
- 5 mm Tempered glass
- Rear Door - 1.2 mm galvanized steel
- Side Panel - 1.2 mm galvanized steel
- Mounting Pole - 2.0 mm galvanized steel with Zinc Coated

**Surface Finishing :**

Electro Static powder coated, black (RAL9004)

**Maximum Load Capacity :**

Static loading : 1000 kgs.

**Scope of Delivery :**

Cabinets are packed in cartons.