

WALL RACK



G-Series



W-Series

Features :

- Intended for indoor installations.
- Available in 3 usable heights and 3 depths (see reference chart)
- The design of the cabinet is based on dismantlable frame with tempered glass (G-Series) or steel perforated (W-Series) front door and removable rear and side panels with locker and special provided slide lock for side panels.
- Standard version is equipped with 4- adjustable poles 19" mounting angles, blank plate cover the cable entry point.
- Vented raised roof cover can be mounted the fan sets.
- Side panels is easy to remove by slide lock and security lock for install and maintenance.
- Provided with earthing connections.
- Cable entry from the roof and the bottom.
- Cabinets can be fastened directly to the wall without using any brackets –convenient internal access to wall-fixing screws.
- Easy change of door opening direction and opening layout by 180-rotating
- Wide range of supplementary accessories : shelves, drawers, fan Sets, power distribution unit.

Technical Data :

Material :

Frame	-	1.2 mm thick sheet steel
Rear and Side Panels	-	1.0 mm thick sheet steel
Solid blanking plate	-	1.0 mm thick sheet steel
Glass door	-	5.0 mm thick safety glass
Wave perforate door	-	1.2 mm thick sheet steel
Mounting Pole	-	1.5 mm galvanized Steel with zinc Coated

Surface Finishing :

Electro Static powder coated, black (RAL9004)

Standards :

Comply with ANSI/EIA-310D, IEC297-1, IEC297-2, BS5954 Part : 2, DIN 41494

Scope of Delivery : Cabinets are packed in cartons.

U Height (U=44.45 mm.)	Width (mm.)	Depth		Order Number	
		(mm.)	Part	G-Series	W-Series
6U	600	400	Single	CW1-60406G	CW1-60406W
	600	500	Double	CW2-60506G	CW2-60506W
	600	600	Double	CW2-60606G	CW2-60606W
9U	600	400	Single	CW1-60409G	CW1-60409W
	600	500	Double	CW2-60509G	CW2-60509W
	600	600	Double	CW2-60609G	CW2-60609W
12U	600	400	Single	CW1-60412G	CW1-60412W
	600	500	Double	CW2-60512G	CW2-60512W
	600	600	Double	CW2-60612G	CW2-60612W