

WALL RACK

G2 SERIES



19"GERMANY[®]
EXPORT RACK



FEATURES

- ◆ **Designed and Manufactured** To comply Standards of ANSI/EIA-310D-1992 (Rev.EIA-310C), IEC60297-1, IEC60297-2, BS5954 Part:2, DIN 41494, 19" Standard.
- ◆ **3-Part Designed** Front Door, Central Part and Back Base.
- ◆ **Manufactured** Made from 1.2mm Electro-Galvanized Steel Sheet and 2.0mm for mounting pole, 100% rust proof.
- ◆ **Mounting Pole** Designed to be L-shape angle with 10x10mm square punching hole to increase strength and flexible to adjust freely with screened Rack unit (U) on the mounting pole.
- ◆ **Front Door**
 - For G2-XXXXXN model was the steel frame with acrylic 5.0mm thickness and 38 cm width, with film protection (About the height will follow as the size of Rack unit). Door edge with 3-fin type of dust proof rubber seal (Gray color). Support security lock with 19" Germany master key, and trademark embossing on the top.
- ◆ **Center Part** There is sliding rail to adjust the mounting pole. The bottom equipped with special rollers for opening and locking to back base part. The top has pre-punch fan pattern for mounting the fan sets (1-3 fan sets for installation). The both side have ventilation grill and support security locking system with 19" Germany master key same as the front door.
- ◆ **Back Base** There is the clip with 10x10mm for cable access at the top and bottom and can be mounting to the wall with screws by 2.4mm thickness two plies steel on the rear part.
- ◆ **Hinge** Made from 3 pieces of special high strength PVC (ABS) or other materials (as requested), without disturbance noise and rust-free. The front and rear door can reverse to change the opening direction from the left or right side by adjusting screw at the nut of hinge.
- ◆ **Grounding System** 2.5mm copper wire with yellow and green color stripe which connect between cabinet's structure and door.
- ◆ **Color** Black painted by by Electrostatic powder coat system with international standards ASTM-D3363, ASTM-D3359, ASTM-D522.
- ◆ **Screw Set** Provided screws, captive nuts, plastic washer with nickel plating and M6 standard.
- ◆ **Manufacturer and Distributor** Certified by ISO 9001 : 2015.
- ◆ **Index of Protection** IP 40



Master Key w/logo




Roller



Mounting Pole



Hinge w/logo



Two Plies Steel

Options

Pole : 4 Poles

Delivery with

- 3 Master key with key number and trademark embossing
- 4 Sets of wall mounting screw.
- Nut and screw sets according to no. of Rack unit (U).

ORDERING INFORMATION W=Width 600 mm. Standard

1U = 44.45 mm. Height (mm.)	Overall	Order No. of Different Depth (mm.)		
		D = 400	D = 500	D = 600
6U	320	G2-60406N	G2-60506N	G2-60606N
9U	455	G2-60409N	G2-60509N	G2-60609N
12U	590	G2-60412N	G2-60512N	G2-60612N