

Mode	1 input, 4 output	
HDMI Performance [®]	Compatibility	HDMI 1.4, HDCP1.4
	Resolution	800x600、1024x768、1280x720、1280x960、1366x768、1440x900、1680x1050、1920x1080、480i@60Hz、480p@60Hz、576i@50Hz、576p@50Hz、720p@50/60Hz、1080i@50/60Hz、1080p@24/25/30/50/60Hz、4K@24/25/30Hz
	Audio Formats	PCM、LPCM、DTS-HD、DTS-Audio
Transmission distance	CAT6/6A/7	1080p@60Hz≤70 meters 4K@30Hz≤40 meters
IR Passback	Bi-directional IR passback (20-60khz)	
RS-232	3Pin : GND-RxD-TxD, follows RS-232 levels Default baud rate : 9600	
Operating Environment	Working temperature	-20~60°C
	Storage temperature	-30~70°C
	Humidity	0~90% RH
Protection	ESD protection 1a Contact discharge level 2 (±4KV) 1b Air discharge level 3 (±8KV) Implementation of the standard: IEC61000-4-2	
	Lightning protection	
	Surge protection	
Power	Supply	TX: DC12V/2A RX: DC5V/1A
	Consumption	TX<10W RX<2.5W
Physical Properties	Housing	Iron
	Color	Black
	Weight	TX: 435g RX: 160g x4
	Dimensions	TX: 191.5(L) x 96.5(W) x 19.0(H)mm RX: 75.0(L) x 80.0(W) x 18.0(H)mm