

PSG-3104

4-Port Gigabit PoE Switch (60W)



PSG-3104

Introduction

PSG-3104 desktop switch is a new design of 5 ports unmanaged PoE switch, provides 1 independent uplink port, and 1-4 ports support IEEE802.3af/at. Suitable for monitoring engineering and network engineering, can supply power for wireless AP, IP cameras and other equipment, plug and play, provides a low cost and high performance network solution.

Main feature

- L2 unmanaged switch
- 5x10/100/1000Mbps RJ45 port, Auto MDI/MDIX
- Support IEEE 802.3, IEEE 802.3u, IEEE 802.3ab standard
- Support IEEE 802.3x flow control
- Provide 8K MAC address
- Store-and-Forward mode
- Non modular structure
- Plug and Play
- Provide 1-4port PoE power supply, each port maximum power 30W
- The total power of 60W

Product Specifications

Specifications

Standard Compliance	IEEE 802.3 10Base-T (Ethernet) IEEE 802.3u 100Base-TX (Fast Ethernet) IEEE 802.3ab 1000Base-T (Gigabit Ethernet) IEEE 802.3x Flow Control (full-duplex flow control) IEEE 802.3af/at (PoE/PoE+ Standard) IEEE 802.3az : Energy-Efficient Ethernet
Ports	4x10/100/1000Base-T, RJ45 port (with PoE and auto MDI/MDI-X) 1x10/100/1000Base-T, RJ45 port (auto MDI/MDI-X, for uplink)
Switch Fabric (Backplane Bandwidth)	10Gbps
Transmit Rate	7.44Mpps
Packet Buffer Memory	4Mbits
Jumbo Frames	10KBytes
MAC Address	8K
Transmission Method	Store and Forward
Transmission Cable	10Base-T Cat. 5e UTP/STP or better 100Base-TX Cat. 5e UTP/STP or better 1000Base-T Cat. 5e UTP/STP or better
PoE	Provide 1-4 port PoE power supply, each port maximum power 30W.
LED Status	Power, PoE, Link/Act
Power Requirements	100-240 VAC, 50-60Hz
PoE Consumption	60 Watts
Dimension	180 × 280 × 44mm (L x W x H)
Environment Temperature	Operate: 0 to 50°C Storage: -10 to 70°C
Environment Humidity	Operate:10 to 85% (RH non-condensing) Storage:10 to 90% (RH non-condensing)
Certifications	FCC and CE



AMERICAN STANDARD

*Specifications subject to change without notice.