

Ruijie | 睿捷 Rcycc

# RG-EW1200

## 1200Mbps Dual-band Gigabit Wireless Router

DATASHEET



### Highlights

- Support 802.11ac wave2
- 4 Omnidirectional antennas provide strong Wi-Fi signal
- Concurrently support up to 96 devices connection
- Reye Mesh builds up flexible multi-solutions for your network
- Easy network management at your fingertips with Reye Router App

## Specifications

### Basic

Dimensions ( WxDxH )	182 mm x 120 mm x 32 mm (7.17 in. x 4.72 in. x 1.26 in. antennas not included)
Weight	0.22 kg (packages not included)
Wi-Fi Standards	Wi-Fi 5 (802.11ac)
MIMO	2.4 GHz, 2x2, MU-MIMO 5 GHz, 2x2, MU-MIMO
Max. Wi-Fi Speed	2.4 GHz: 300 Mbps 5 GHz: 867 Mbps
Channel Width	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80 MHz
Antennas	4
Antennas Type	External Omnidirectional
Antenna Gain	2.4 GHz: 5 dBi 5 GHz: 5 dBi
WAN Port	1x10/100 Base-T Port
LAN Ports	3x10/100 Base-T Ports
Recommended Users	24
Max. Users	96
Power Supply	DC 12V/0.6A
Power Consumption	≤8.2W
Operation Frequency Bands	802.11b/g/n: 2.400 GHz to 2.483 GHz 802.11a/n/ac: 5.150 GHz to 5.350 GHz 802.11a/n/ac: 5.470 GHz to 5.725 GHz , 5.725 GHz to 5.850 GHz country-specific restrictions apply
Transmit Power	Regular: CE EIRP: ≤20 dBm (2.4 GHz) ≤27 dBm (5 GHz)
Operating Temperature	0 °C to +45 °C (32 °F to 113 °F)
Operating Humidity	5% to 95% Noncondensing
Certifications	CE, RoHS

## Specifications

Wireless	
OFDMA	-
MU-MIMO	✓
BSS Coloring	-
Maximum Number of SSIDs	6
SSID Hiding	✓
Band Steering	✓
Guest Wi-Fi	✓
WPA/WPA2	✓
WPA3	-
Roaming	Layer 2 Roaming
Blacklist	✓
Reyee Mesh	✓
Mesh Pairing by Hardware	✓
Mesh Pairing by Mesh Button	✓
Mesh Pairing by Eweb	✓
Recommended Hop Count	≤5
Wi-Fi Optimization	✓
QoS (WMM)	✓
WPS	-
Transmission Power Adjustment	✓
Hardware	
CPU	MT7628
Flash	16M

## Specifications

### Hardware

RAM/SDRAM	64M
Color	White
System LED Indicator	✓
Reyee Mesh LED Indicator	-
Reyee Mesh Button	✓
Power Button	-
Reset Button	✓
DC Connector Dimensions	5.5 mm x 2.1 mm x 10 mm (0.22 in. x 0.08 in. x 0.39 in. antennas not included)

### WAN

Static IP	✓
DHCP	✓
PPPoE	✓
Learning PPPoE Account & Password	✓
VLAN Tagging	✓

### LAN

DHCP Server	✓
Client List	✓
Static IP Assignment	✓
Port-Based Flow Control	✓

### Features

IPv6	✓
DDNS	✓
IPTV	✓

## Specifications

Features	
Alarm	✓
Diagnosis	✓
UPnP	✓
ARP Binding	✓
Port Mapping	✓
DMZ Host	✓
Rate Limitation of Terminals	✓
Hardware Acceleration	✓
MAC Address Cloning	✓
Cloud Management	✓
Repeater Mode	✓
WISP Mode	-
Security	
PPTP VPN Server	-
PPTP VPN Client	✓
L2TP VPN Client	-
Parental Control	✓
Protect TCP Flood Attacks	✓
Protect ICMP Attacks	✓
Protect UDP Flood Attacks	✓
System	
Default Access/Password	192.168.110.1 No Password Required by Default
URL Access	✓

## Specifications

System	
Local Upgrade	✓
Online Upgrade	✓
APP Upgrade	✓
Syslog	-
Backup	✓
Factory Reset	✓
Language	Chinese English Vietnamese Indonesian Thai Arabic Traditional Chinese Spanish Russian

## Package Contents

Model	RG-EW1200
Wireless Router	1
Power Adapter	1
Quick Start Guide	1
Cat5e UTP Cable	1

Ruijie | 锐捷 Rcycc

 Redefine your easy network



Ruijie Networks Co., Ltd  
Floor 11, East Wing, Zhongyipengao Plaza,  
No.29 Fuxing Road, Haidian District, Beijing China  
Website: <https://www.ruijienetworks.com>