


VENTILATING FAN



Power Cord



Plastic Guard



Impeller



Frame



A



B



C

FEATURES

- ◆ Provides natural air convection within the cabinet.
- ◆ Two ball bearing heavy duty type with glass fiber reinforced plastic Impeller complied to UL 94V-0 rating and impedance protected.
- ◆ 120 x 120 x 38 mm. die-cast aluminum housing with black ABS plastic guard 7.0 mm. thickness with embossed trademark 19"Germany Export Rack.
- ◆ Frame for 2 x 4" & 3 x 4" Fan set made from Electro-Galvanized sheet steel, light gray colour Electrostatic powder coating.
- ◆ Power cord, 1.80 m. for individual fan and 1.40 m., 3C x 18AWG with ground for 2 x 4" and 3 x 4" fan set.
- ◆ Assembly and Distribution by ISO 9001:2008 Company.

Technical Specification

- Speed : 2,400 rpm
- Max air Flow : 2.01 m³/min or 72 CFM
- Operating Temp. : - 30°C to + 70°C
- Input Voltage : 220VAC/50Hz
- Max Power : 11 W
- Life Expectancy : 50,000 Hours Continuous
- Approvals : CE & UL/CSA

Options

- Color : Black

ORDERING INFORMATION

Order No.	Description	Figure
G7-05001	1 x Ø 4" HEAVY DUTY FAN (Individual) w/Cable 1.8 M	A
G7-05002	2 x Ø 4" HEAVY DUTY FAN SET w/Cable 1.4 M	B
G7-05003	3 x Ø 4" HEAVY DUTY FAN SET w/Cable 1.4 M	C

* Order No. for Black Color : G7-050XXB

Sample : G7-05002B 2 x Ø 4" HEAVY DUTY FAN SET w/Cable 1.4 M., Black Color